DOCKET: 915-001.096

## IN THE CLAIMS:

- 1. (Currently Amended) A method for transmitting data from a receiving first mobile station, from which there is defined a call divert command to anothera second mobile station, to said second mobile station, eharacterized in that comprising
- [[-]] there is identified identifying the first mobile station, from which data is being transmitted for said transmitting data to the second mobile station-(101), and
- [[-]] in case the data transmitting mobile station is identified as the first mobile station, from which there is defined a call divert command to the second mobile station, receiving the data is received in the second mobile station (102), or
- [[-]] in case the data transmitting mobile station is identified as other than the first mobile station, from which there is defined a call divert command to the second mobile station, <u>transmitting</u> the data is <u>transmitted</u> to a predetermined receiver (103).
- 2. (Currently Amended) A method according to claim 1, characterized in that the first mobile station, from which data is being transmitted to the second mobile station, is identified by a network device (303,305) before transmitting the data to the receiversecond mobile station, and the receiversecond mobile station is selected according to the identified transmittertransmitting mobile station by said network device (303,304, 305).
- 3. (Original) A method according to claim 1, characterized in that the first mobile station, from which data is being transmitted to the second mobile station, is identified in the second mobile station (205,206) before activating the data in the

second mobile station, and according to the identified transmitter, the data is received in said second mobile station, or it is transmitted further to a predetermined third receiver.

- 4. (Currently Amended) A system for transmitting data from a first mobile station to a second mobile station as a response to a call divert command in the first mobile station, characterized in that the system comprises:
- [[-]] means an identifying element for identifying the a data transmitting device from which data is being transmitted to the receiving second mobile station (101,206, 303,501),
- [[-]] means a receiving element for receiving data in the second mobile station-(102,201, 202,205), in case the data transmitting device is identified as that mobile station, from which data, according to the call divert command, is transmitted to the receiving second mobile station, and
- [[-]] means a further transmitting element for transmitting data further to a predetermined third receiver-(103, 502,503, 504,505, 506,507), in case the data transmitting device is identified as other than that mobile station from which data, according to the call divert command, is transmitted to the receiving second mobile station.
- 5. (Currently Amended) A system according to claim 4, characterized in that wherein it includes means an identifying element for identifying that previous device from which the data was last transmitted (101).
- 6. (Currently Amended) A system according to claim 4, eharacterized in that wherein it includes means a redefining element for redefining the receiver information of the transmitted data based on the basis of predefined receiver information (206,303), as

a response to identifying the data transmitting device as other than that mobile station, from which data, according to the call divert command, is transmitted to the receiving second mobile station.

- 7. (Currently Amended) A system according to claim 4, characterized in that wherein it includes means a redefining element for redefining the data receiver information based on the basis of the data type, according to predetermined instructions (206,303), as a response to identifying the data transmitting device as other than that mobile station from which data, according to the call divert command, is transmitted to the receiving second mobile station.
- 8. (Currently Amended) A system according to claim 4, eharacterized in that wherein the system means elements are software means (206,303, 305) elements.
- 9. (Currently Amended) A system according to claim 4, eharacterized in that wherein the system is a mobile communication network, and that the means elements are located in thea message and/orcenter or a mobile switching center-(303), or both.
- 10. (Currently Amended) A system according to claim 4, eharacterized in that wherein the system is a network, and the means elements are located in a network gateway bus (502a, 503a, 504a, 505a, 506a, 507a).
- 11. (Currently Amended) A system according to claim 4, <del>characterized in that</del> wherein the system is a network, and that the <del>means</del> elements are located in a network terminal device (301,501).

- 12. (Currently Amended) A mobile station, in which there is defined a call divert command from another mobile station, so that the mobile station receives data designated to said second mobile station, characterized in that the mobile station (301) includes
- [[-]] means an identifying element for identifying that a data transmitting device, from which data is being transmitted to the mobile station (205,206),
- [[-]] means a receiving element for receiving the data in the mobile station (201,202, 205,203a, 203, 204a, 204,207, 209), in case the data transmitting device is identified as that second mobile station, from which data, according to the call divert command, is transmitted to the mobile station, and
- [[-]] means a transmitting element for transmitting data further to a predetermined third receiving party-(201,202, 205,206), in case the data transmitting device is identified as other than that second mobile station, from which data, according to the call divert command, is transmitted to the mobile station.
- 13. (Currently Amended) A mobile station according to claim 12, eharacterized in that the wherein a mobile station (301) that receives the a request for establishing a connection includes means an identifying element for identifying the a telephone number transmitting the request for establishing a connection as that telephone number from which the call divert is defined (202,205, 206,209).
- 14. (Currently Amended) A mobile station according to claim 12, eharacterized in that it (301) includes means wherein it includes an establishing element for establishing a connection between the mobile station (MS1) transmitting thean original request for establishing a connection and thea mobile station (MS11) receiving the request for establishing a connection.

- 15. (Currently Amended) A mobile station according to claim 12, eharacterized in that wherein the mobile station (301) includes means a rerouting element for rerouting the a request for establishing a connection based on the basis of the an identified telephone number transmitting the request for establishing a connection (206).
- 16. (Currently Amended) A mobile station according to claim 12, eharacterized in that it (301) includes means wherein it includes a receiving element for receiving a message in a mobile station (201,202, 205), as a response to identifying thea previous data transmitting device as that second mobile station from which data, according to the call divert command, is transmitted to the mobile station.
- 17. (Currently Amended) A mobile station according to claim 12, eharacterized in that wherein the mobile station (301) includes means a redefining element for redefining (206) the receiver of a message and means a transmitting element for transmitting the message further to said a redefined receiver (201,202, 205) as a response to identifying the a previous data transmitting device as other than that second mobile station from which data, according to the call divert command, is transmitted to the mobile station.
- 18. (Currently Amended) A mobile Mobile switching center for transmitting data as a response to detecting a call divert command, characterized in that the mobile switching center (303)-includes
- [[-]] means an identifying element for identifying that a data transmitting device from which data is transmitted to the receiving second mobile station (303),
- [[-]] means a transmitting element for transmitting data to the second-mobile station (302,303, 304, 305), in case the data transmitting device is identified as that a mobile station from which data, according to the call divert command, is transmitted to the receiving second-mobile station, and

- [[-]] means a transmitting element for transmitting data to a predetermined thirdother receiver (302,303, 304, 305), in case the data transmitting device is identified as other than that mobile station from which data, according to the call divert command, is transmitted to the receiving second-mobile station.
- 19. (Currently Amended) A mobile switching center according to claim 18, eharacterized in that wherein the center (303) looks is able to look up in thea network home register (305) information for identifying thea previous transmitter of the data and for defining thea receiver according to thean identified transmitter.
- 20. (Currently Amended) A mobile switching center according to claim 18, eharacterized in that wherein the center (303) includes means a redefining element for redefining (303,305) the data receiver information as a response to identifying the data transmitting device as other than that mobile station from which data, according to the call divert command, is transmitted to the receiving second mobile station, and means a rerouting element for rerouting the transmitted data to said a redefined receiver (303,305).
- 21. (Currently Amended) A mobile switching center according to claim 18, eharacterized in that wherein it includes means an establishing element for establishing an active connection between the original data transmitter (MS1) and the data receiver (MS11).
- 22. (Currently Amended) A mobile switching center according to claim 18, characterized in that wherein the center (303) includes means a transmitting element for transmitting a given data entity to the receiver.

- 23. (Currently Amended) Software meanselement for processing the data to be transmitted for transmission as a response to detecting a call divert command, characterized in that they include comprising
- [[-]] software meanselement for identifying that a data transmitting device from which data is being transmitted (101),
- [[-]] software meanselement for transmitting data to the receiver according to the call divert command-(102), in case the data transmitting device is identified as that mobile station from which data, according to the call divert command, is transmitted to the receiver, and
- [[-]] means a transmitting element for transmitting data to a predetermined third other receiver (103), in case the data transmitting device is identified as other than that mobile station from which data, according to the call divert command, is transmitted to the receiver.
- 24. (Currently Amended) Software means element according to claim 23, eharacterized in that the software means are located in a network unit (303,305).
- 25. (Currently Amended) Software means element according to claim 23, eharacterized in that the software means are located in a network gateway bus (502a, 503a, 504a, 505a, 506a, 507a).
- 26. (Currently Amended) Software means element according to claim 23, eharacterized in that the software means are located in a terminal device (301,501).